

Agilent 4073A Test Systems (JAD-37247)

Make: Advantest
Model: 4073A
Quantity: 1
Vintage: 2000
Inspection: Available

Configuration:

Model			4073A
Module name		Description	
Pinboard		Used to contact with prober card, number is defined by prober card max pin Qty is 48 , if you order HRSMU, you must use HR pin board.	
HR pinboard			E3122-66501 *45
Source Monitor Unit, Max Qty is 8	Medium power SMU	10fA current measurement resolution, 2uV voltage measurement resolution, max Voltage 100V, max Current 100mA	3
	High Resolution SMU	1fA current measurement resolution, 2uV voltage measurement resolution, max Voltage 100V, max Current 100mA	1
	High Power SMU	10fA current measurement resolution, 2uV voltage measurement resolution, max Voltage 200V, max Current 1A	1
Digital Voltage meter		1uV voltage measurement resolution, used for 1ohm level resistant measurement	NA
CV measurement unit	LCR meter	DC Bias Voltage: ±40V,	Agilent 4284A*1
Signal Analyzer		used for Ring Oscillator evaluation	NA
HV-SPGU		Pulse Generator two channel per Qty, selected if pulse is needed.	Agilent 8114A *1
SPECS-FA		For Factory automation	NA

888 E. Belvidere RD, Suite 213 Grayslake, IL 60030 USA

Telephone: +1-847-223-1804