



Your Reliable and Trustworthy Surplus Equipment Market Partner... Worldwide

Nextest Magnum II PV Test System (JAD-38644)

Make: Teradyne/ Nextest
Model: Magnum II PV
Vintage: 2017
Quantity: 1
Inspection: No, tools are crated.

Configuration:

- **(4) SAB 511501**
- **(1) HOB 513182**
- **(1) IPC firmware 5.4.14**

Includes:

- **Workstation: Dell T5810**
- **Manipulator: Esmo Tian Ma**

Intel(R) Pentium(R) M processor 1.80GHz, 995MB total physical memory.
 Microsoft Windows XP
 2600.xpsp.080413-2111

- Revision Codes for Boards -

*** Summary of board set for SA pn: 511501 ***

*** Summary of option board set for HOB5 Assembly pn: 513182 ***

Board Name	Serial Number	PWB Number	PWB Rev	Site 1 (Chassis 1, Slot 1)		LVM SDR/DDR	DBM GBits	ECRM GBits	ECSR GBits	RCM MBits	X bits	Y bits	D bits
				PWA Number	PWA Rev								
HSB2		508262	2	508263	12	64/128	(4) 18 (2)	36 (4)	36 (4)	36 (2)	24*	24*	36*
PE32_1		511264	3	511265	7								
PE32_2		511264	3	511265	7								
PE32_3		511264	3	511265	7								
PE32_4		511264	3	511265	7								
DPX20_1		504582	9	508488	9								
DPX20_2		504582	9	508488	9								
DPX20_3		504582	9	508488	9								
DPX20_4		504582	9	508488	9								
IPC		509681	2	509680	20	Firmware Revision : 5.4.14							
HOB_5		509988	3	513747	5								
DPONV_1		512543	1	512545	17								
DPC_1		513555	2	513554	2								
HVI_1		513176	3	513175	5								
DPONV_2		512543	1	512545	17								
DPC_2		513555	2	513554	2								
HVI_2		513176	3	513175	5								
DPONV_3		512543	1	512545	17								
DPC_3		513555	2	513554	2								
HVI_3		513176	3	513175	5								
DPONV_4		512543	1	512545	17								
DPC_4		513555	2	513554	2								
HVI_4		513176	3	513175	5								
DPONV_5		512543	1	512545	17								
DPC_5		513555	2	513554	2								
HVI_5		513176	3	513175	5								
DPONV_6		512543	1	512545	17								
DPC_6		513555	2	513554	2								
HVI_6		513176	3	513175	5								
DPONV_7		512543	1	512545	17								
DPC_7		513555	2	513554	2								
HVI_7		513176	3	513175	5								
DPONV_8		512543	1	512545	17								
DPC_8		513555	2	513554	2								
HVI_8		513176	3	513175	5								

* NOTE: The ECR X, Y, D bits represent the maximum allowable configuration.

* NOTE: This tester is properly configured to support the 300mA/600mA DPS option.

